



Model	SM 220-440H*	SM 220-440O*	SM 220-550H*	SM 220-550O*	SM 220-660H*	SM 220-660O*	SM 340-880H*	SM 340-880O*	SM 340-1100H*	SM 340-1100O*
Masa operacyjna koparki [t]	14 - 20	14 - 20	18 - 23	18 - 23	22 - 30	22 - 30	24 - 32	24 - 32	30 - 40	30 - 40
Pojemność [dm3]	400	400	500	500	600	600	800	800	1000	1000
Masa (z rotatorem) [kg]	1070	1020	1250	1200	1400	1350	1750	1700	2480	2400
Max. ciśnienie robocze [bar]	320	320	320	320	320	320	350	350	350	350
Liczba pazurów	5	5	5	5	5	5	5	5	5	5
Wymiary [mm]										
- A	1260	1260	1380	1380	1535	1535	1640	1640	1940	1940
- B	2060	2060	2160	2160	2260	2260	2360	2360	2590	2590
- C	1915	1915	2105	2105	2300	2300	2510	2510	2780	2780
- D	1640	1640	1810	1810	1990	1990	2030	2030	2250	2250
- E	1755	1755	1790	1790	1820	1820	1910	1910	2320	2320

H - pazury półotwarte ; O - pazury otwarte